

# A5

Automatic  
Dispenser



- ➔ 1L/min High efficiency  
suitable For batch  
dispensing
- ➔ 1/2000Y High accuracy  
suitable For sample  
paint dispensing
- ➔ 100% Recirculation  
suitable For Z-VOC  
colorant

● Electric can table

**SANTINT • CHINA**

Add: Feilong Road, Xingyang,  
Zhengzhou, China  
Email: info@santint.com

**SANTINT • HOLLAND**

Add: Lageweg 35 - J. 2222 AG  
Katwijk The Netherlands  
Email: sales@santint-europe.com

**SANTINT • POLAND**

Add: ul. Postepu 19. mag.5  
02-676 Warszawa Polska  
Email: albert@santintpoland.com

**SANTINT • U.S.A**

Add: 2000 Bloomingdale Road,  
Suite 205, Glendale Heights,  
IL 60139, U.S.A  
Email: dino@santintusa.com

**SANTINT • BRAZIL**

Add: Rua Rosa Kasinski,  
1109 (Galpão 30) - Capuava  
- Cep: 09380-128 - Mauá / Sp  
Email: marcos@santint.com

**SANTINT • INDIA**

Add: Building No.E3, 2/3, Hari  
Hari Compound, Near Gajanan  
Petrol Pump, Mankoli Nana,  
Bhiwandi 421302 Thane India  
Email: nick@santint.com

# A5 Main Features >>>



## 1 Reduces customer waiting time

High efficiency piston pump shortens tinting time.



## 2 Suitable for sample paint dispensing

Small pump and small nozzle inside achieve 1/2000Y (0.015ml) super high accuracy, suitable for sample paint dispensing.



## 3 Suitable for Z-VOC colorant

100% recirculation patented technology. In the standby time, the colorant is completely isolated from air; timed recirculation makes the colorant noncondensing and prevents the nozzle from dryness and blockage & colorant from deterioration.

## 4 LCD timely displays machine status

## 5 Weight feedback function optional

Electronic scale real-time feedbacks dispensing amount. Accurate compensation can be achieved according to feedback value. It applies to industrial paint, ink, automotive paint, etc.

### ■ Canister configuration

16 canisters: 12 X 2.3L + 4 x 6L  
24 canisters: 12 X 2.3L + 12 x 2L

### ■ Pump configuration: sequential piston pump

■ Flow rate: 3.8L/min

### ■ Efficiency: 1L/min

■ Accuracy: 0.015ml

### ■ Applicable can: diameter ≤ 350mm, height ≤ 420mm

### ■ Can table: manual, electrical optional

■ Mixing Speed: 20-25r/min

### ■ Machine Dimension (W\*D\*H): 830 x 985 x 1295mm

### ■ Packing Dimension (W\*D\*H): 900 x 1070 x 1480mm

### ■ Net Weight: 240Kg(Electrical) 220Kg(Manual)

### ■ Gross Weight: 300Kg(Electrical) 280Kg(Manual)

### ■ Power Supply: 220V/110V 50HZ/60HZ

# A5

## Technical Parameters

