AC100 Automatic Dispenser

Dispensing Mode	Automatic Dispensing	Max Can Size (D x H)	200 x 180mm (with scale) 200 x 280mm (without scale)
Efficiency (single toner)	200ml/min or 300ml/min		
Minimum Shot	1/2000Y(0.015ml)	Machine Dimension (W X D X H)	1770X1215X1400mm (96 toners)
Pump Capacity	60ml/90ml (Optional)	Heating Module	Optional
Stirring Speed	20-25rpm	Net Weight	650kg
Canister Size	84x1.25L+12x4.3L	Power	≤350W
No. of Canisters	Up to 96	Power Supply	220V/110V 50Hz/60Hz

SANTINT • CHINA
Add: Feilong Road, Xingyang, Zhengzhou, China
Email: info@santint.com

SANTINT • HOLLAND
Add: Lageweg 35 - J, 2222 AG Katwijk The Netherlands
Email: sales@santint-europe.com

SANTINT • POLAND
Add: 19 Postępu Street (warehouse no. 5)02-676 Warsaw, Poland
Email: albert@santintpoland.com

SANTINT • U.S.A
Add: 2000 Bloomingdale Road, Suite 205, Glendale Heights,IL 60139, U.S.A
Email: dino@santintusa.com

SANTINT • INDIA
Add: Building No.E3 , 2/3 , Hari Hari Compound, Near Gajanan Petrol Pump, Mankoli Nana,Bhiwandi 421302 Thane India
Email: nick@santint.com

SANTINT• BRASIL
Add: Rua Rosa Kasinski, 1109 (Galpão 30) - Capuava - Cep: 09380-128 - Mauá / Sp
Email: contato@santint.com

SANTINT• AUSTRALIA
Add: 3 Technology Circuit Hallam Victoria, Australia
Email: Info.AU@santint.com

SANTINT
WHERE INNOVATION MEETS PRECISION

WELCOME TO AUTOMATIC CAR-REFINISH TINTING ERA

High Return · Simple Maintenance · High Efficiency

Automatic Dispenser AC100

HOW TO TINT

1. Spectrophotometer Reading

2. Formula Creating or Selecting





3. Automatic Dispensing

4. Color Comparing

OTHER FEATURES

Heating (Optional)
Keep toners in an environment of 8-15 °C

Low Maintenance Nozzle
Inventive patent 100% recirculation technology
Purge free and residue free



Clean Tinting Area
No more paint spillage

Repeatable Accuracy
Minimum Shot : 1/2000Y(0.015ml) with one-time calibration



Automatic Stirring
To prevent sedimentation of the toners

Toners Last Long
Single direction valve + sealing ring effectively prevent toners from volatilizing

ROAMING INTO THE NEW ERA TO

Save labor cost
Increase efficiency
Eliminate mistints